

# B-NIMIS BC-PI PRIME

## INFORMATION TECHNICAL DATA

P. 1/2

B-Nimis BC-Pi Prime	Specification			
	Description	BC-Pi Prime S01	BC-Pi Prime S02	BC-Pi Prime S03
Order number	<b>S-01080102-0100</b>	<b>S-01080102-0200</b>	<b>S-01080102-0300</b>	
Dimensions WxHxD [mm]	58 x 122 x 87			
Mounting	Rail mounting NS 35/7,5 EN 50022			
Certification	CE (EN 61131-2)			
Development environment	Raspberry OS			
	Compatible with Raspberry community			
CPU	BCM 2711, 1,5 GHz Quadcore			
RAM / Flash / Retain	1GB RAM / 8GB Flash / 200 KB Retain	2 GB RAM / 8 GB Flash / 200 KB Retain	4 GB RAM / 32 GB Flash / 200 KB Retain	
Communication interfaces	1x Ethernet 10/100/1000 Base, RJ45			
	1x EtherCAT LVDS			
	- WLAN / Bluetooth (optional)			
Protocols	EtherCAT Master and others available via third party suppliers			
Visualization	via display interface			
	2x Host USB 3.0 / USB plug type A			
Additional features	2x Host USB 2.0 / USB plug type A			
	1x digital display interface			
	1x 2 Pin JST for cooling fan (5V)			
	1x Real Time Clock, 72h Puffer			
	Extension: Heat sink (Option: H002)			
	Extension: Fan (Option: H003)			
Supply voltage	+24 VDC (-15% / +20%) SELV max. AC voltage component 5% with reverse voltage protection			
Current consumption	Type 0.5A, max. 2A at +24 VDC			
Operating conditions Transport / storage	Ambient temperature: : Operational: -10 °C bis 45 °C (without additional cooling) / Transport -20 °C bis +70 °C Relative humidity: max. 85%, non-condensing			

### You can reach us at:

T: +49.7121.894-0 | E: [controls@berghof.com](mailto:controls@berghof.com)

**Berghof Automation GmbH** | Arbachtalstraße 26 | 72800 Eningen u.A.  
[www.berghof-automation.com](http://www.berghof-automation.com) | Subject to changes and errors.



# B-NIMIS BC-PI PRIME

## INFORMATION TECHNICAL DATA

P. 2/2

B-Nimis BC-Pi Prime	Specification		
	BC-Pi Prime S01	BC-Pi Prime S02	BC-Pi Prime S03
Emitted interference	EN 61000-6-4, Industrial area		
Immunity to interference	EN 61000-6-2, Industrial area		
Protection class	III		
Insulation strength	SELV (Uw < 30 V) according EN 61131-2		
Protection type	IP20		

### You can reach us at:

T: +49.7121.894-0 | E: [controls@berghof.com](mailto:controls@berghof.com)

**Berghof Automation GmbH** | Arbachtalstraße 26 | 72800 Eningen u.A.  
[www.berghof-automation.com](http://www.berghof-automation.com) | Subject to changes and errors.

